

DESCRIPTION

Gulf Western Truck & Farm Grease is a very high quality extreme duty application tacky complex soap grease. It is suited to nearly all heavy duty greasing applications for agriculture, trucking, automotive, marine, industrial and earthmoving applications. It is formulated with a high base oil viscosity that offers excellent water washout and weld load properties. It is formulated from a combination of polybutene base stocks combined with lithium complex thickener, extreme pressure additives and effective rust, oxidation and corrosion inhibitors. Truck & Farm Grease resists water washout and “squeeze out” from surfaces requiring lubrication under load conditions. It has been specially formulated to include a shear stable tackiness agent which unlike other conventional complex soap greases have this extra tenacity for stayput lubrication because of this added adhesive characteristic.

RECOMMENDATIONS

- Truck & Farm Grease is the ideal recommendation for use in extreme heavy-duty applications and where water washout and high thermal resistance are needed. These applications include all industrial, earthmoving, agricultural, automotive and marine equipment. It is also suited in very demanding applications including high temperatures, high and shock loads, dusty and wet environments. Also suitable for bearings, gears, couplings, turntables, pins, hammers, trailer bearings and most other applications as described above. Suitable temperature range is -20-185°C however can work intermittently up to 210°C.

TRUCK & FARM GREASE	TEST METHOD	UNITS
NLGI	-	2
SOAP TYPE	-	Complex Soap
COLOUR	-	Yellow
TEXTURE	-	Smooth, Tacky
PENETRATION @ 25°C -	-	-
WORKED, 60 STROKES	ASTM D217	270
WORKED 100,000 STROKES, CHANGE %	ASTM D217	275
DROPPING POINT °C	ASTM D2265	260+
ROLL STABILITY, PENETRATION CHANGE %	ASTM D1831	+10
LEAKAGE	-	1.5
WATER WASHOUT @ 80°C %	ASTM D1264	<3.5
OXIDATION STABILITY PRESSURE -	-	-
DROP @ 100 HOUR, KPA	ASTM D942	15
TIMKEN, OK LOAD, KG	ASTM D2509	30
4-BALL WELD, KG/F	ASTM D2596	480
4-BALL WELD SCAR, MM	ASTM D2266	0.42
BASE OIL VISC @ 40°C	ASTM D445	800

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

205LT - #60054, 20KG - #62054, 450GM - #60454

January 2023