

TECHNICAL DATA SHEET

SYN-CVT FLUID



DESCRIPTION

Syn-CVT Fluid is a synthetic multi-functional transmission fluid suitable for use in most Continuously Variable Transmissions including those that are chain and belt driven. Syn-CVT Fluid is comparable in quality to genuine CVT fluids however works across multiple vehicle makes and models making it a true universal fluid.

SUMMARY OF BENEFITS

- Suitable for use in nearly all belt, chain and hybrid CVT's excluding some hybrid Toyota and hybrid Ford models
- Excellent shear stability for increased drain intervals
- Improved anti foam properties
- Advanced Anti Shudder durability
- Excellent metal to metal friction performance
- Excellent seal compatibility
- True multi-functional, universal CVT Fluid
- Synthetic formulation
- Excellent low and high temperature properties

SUITABLE FOR



SPECIFICATIONS

- AUDI/VW (TL 52180, G 052 180, G 052 516)
- DODGE/JEEP (NS-2, CVTF+4)
- FORD (CVT30, MERCON C, CVT23)
- GM/SATURN (DEX-CVT)
- HONDA (HMMF, HCF-2)
- HYUNDAI/KIA (SP-CVT 1)
- MAZDA (CVTF, CVT3320)
- MERCEDES BENZ (236.20)
- MINI COOPER (EZL 799A)
- MITSUBISHI (CVTF-J1, CVTF-J4)
- NISSAN (NS-1, NS-2, NS-3)
- SUBARU (NS-2/LINEARTRONIC CVTF, K0425Y0710, CV-30, HIGH TORQUE CVT FLUID)
- SUZUKI (TC, NS-2, CVT GREEN 1, CVT GREEN 2)
- TOYOTA/LEXUS (TC, FE)

SYN-CVT FLUID	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.8570
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	33.7
@ 100°C	ASTM D445	cSt	7.19
VISCOSITY INDEX	ASTM D2270	-	184
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	193
COLOUR	-	-	Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

20LT - #62041, 4LT - #60441

February 2022

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au